
PCB TMDL Monitoring Guidance

VPDES Point Source Discharges



Alan Pollock, Charles Martin & Arthur Butt



VADEQ March 29, 2007

Overview

- Objective
- Background
- Presentation
 - Delaware River Basin Commission

< Lunch >

Guidance Development

- Monitoring & Methods
- Permit Guidance
- Issues
 - Where
 - Who
 - When





Objective

- To establish guidance and procedures for implementing PCB point source monitoring through the VPDES permit program for development of TMDLs.
- Schedule 3 meetings
 - 2nd meeting with draft May
 - Final meeting with guidance document July



Purpose

Develop Total Maximum Daily Load (TMDL)

Collect source-specific PCB effluent to:

- improve information concerning potential sources of PCBs
- develop PCB monitoring procedures
 - ensures representative and comparable
 - adopt sampling and analytical procedures



Role of the TAC Guidance Development

The Technical Advisory Committee (TAC) represents the interested agencies, utilities, local governments, businesses, and environmental groups. The TAC will:


- review methods & processes
- advise on technical issues
- assist with guidance development
- assist with public outreach

Background -Charles Martin

What's the Problem?









1.5 metric tons manufactured worldwide. US production ended in 1977 – banned by EU in 1985 but stockpiles still exist



Legacy Toxicant?

- Scrap Metal salvage yard
- Fluorescent Light Ballasts
- Metal Recycling yard/transfer station
- Oil Recycling facility
- Rail shipping/storage yard
- Concrete facility/product(s)
- Power generating facilities or transformer stations
- Electronic Components
- Flame Retardants in Lubricating Oils
- Natural gas compressor station(s)
- Carbonless copy paper
- Submersible well pumps
- Plasticizers in sealants, caulkings, synthetic resins, rubbers, paints, waxes and asphalts
- MODEF atmospheric











What's a TMDL?



Total Maximum Daily Load

- a pollution budget
- a calculation of the maximum amount of a pollutant that a waterbody can receive and still meet water quality standards
- includes an allocation of that maximum amount to each pollutant source

When are TMDLs needed?

- State and federal law require TMDLs to be developed for impaired waters
- Impaired waters do not meet applicable water quality standards (WQS)
- Waters that do not meet WQS do not support their designated use(s)

How is a TMDL developed?

- Identify all sources of a given pollutant (e.g., PCBs) within the watershed.
- Calculate the amount of pollutant entering the estuary from each source.
- Include pollutant fate and transport.
- Calculate the pollutant reductions
 needed, by source, to attain water quality
 standards.
- Allocate the allowable loading to each source and include a margin of safety.

Definition

Summarized as:

$$TMDL = \sum (WLA + LA) + MOS$$


Where:

TMDL = Total Maximum Daily Load

WLA = Waste Load Allocation (point sources incl. permitted stormwater discharges)

LA = Load Allocation (nonpoint sources)

MOS = Margin of Safety





Fish Consumption

ADVISORY: Fish taken from these waters may contain PCBs. Eat no more than one meal per month of any fish taken from the advisory area. Women who are pregnant or may become pregnant, nursing mothers, and young children should not eat any fish taken from these waters. (5/15/03)

http://www.vdh.state.va.us/hhcontrol/fishing_advisories.htm



VA Criteria

Consumption
Advisories
Fish Tissue
(ng/g)


Water Quality
Standards
Total PCBs (ng/L)

54

1.70 *

PCBs in Fish Tissue for 2006

- 973 River Miles
- 72,000 acres in Lakes
- 2,110 sq miles of Estuarine Waters



PCBs Fish Tissue Impairments - 2006 Assessment -

	River	Estuary	Lakes
Basin	Miles	(sq miles)	(acres)
Chesapeake Bay	0	1,634	534
Poto/Shen	98	30	101
Rappahannock	29	129	0
York River	17	58	9,585
James	209	259	0
Chowan - Dismal	27	0	0
Roanoke	212	0	57,502
Tenn/Big Sandy	274	-	0
New River Basin	108	-	4,287

PCB's

- ☐ Man-made organic chemicals with a biphenyl base structure and 209 possible chlorine substitution patterns.
- ☐ Terminology: aroclors, congeners, homologs.
- ☐ Properties: Hydrophobic, tend to accumulate in sediments and tissues
- Probable liver damage and carcinogen




	TABLE 1	
SPECIFIC PCB	CONGENERS	IN AROCLORS

Congener	IUPAC number	1016	1221	1232	Aroctor 1242	1248	1254	1260
Biphenyl	_		х					
2-CB	1	X	X	X	X			
23-DCB	5	X	X	X	X	X		
34-DCB	12	X		X	X	X		
244'-TCB	28"	X		X	X	X	X	
22'35'-TCB	44			X	X	X	X	X
23'44'-TCB	66*					X	X	X
233'4'6-PCB	110						X	
23'44'5-PCB	118*						X	X
22'44'55'-HCB	153							X
22'344'5'-HCB	138							X
22'344'55'-HpCB	180							×
22'33'44'5-HpCB	170							X

PCB Homologs				
Homolog	Abbreviation	CI Substituents	PCB Congeners	
Monochlorobiphenyl	MoCB	1	3	
Dichlorobiphenyl	DiCB	2	12	
Trichlorobiphenyl	TrCB	3	24	
Tetrachlorobiphenyl	TeCB	4	42	
Pentachlorobiphenyl	PeCB	5	46	
Hexachlorobiphenyl	HxCB	6	42	
Heptachlorobiphenyl	HpCB	7	24	
Octachlorobiphenyl	OcCB	8	12	
Nonachlorobiphenyl	NoCB	9	3	
Decachlorobiphenyl	DeCB	10	1	

Presentation

Greg Cavallo, DRBC





Avoid accidents

&

Protect human health




Issues

- TMDL
 - Regulatory
 - Lacking PCB data
 - Ambient water
 - Effluent
 - Needs
 - Monitoring
 - Ambient
 - Effluent
 - » Voluntary
 - » Permits
 - Options
 - EPA Method 1668A
 - USGS SPMDs



LUNCH

- Monitoring & Analytical Methods
 - Mark Richards



Guidance Development







LUNCH

- break -



Where – Discharges to

All waters



Who -

PCB impaired waters

- Majors
- CSOs
- Minors
- Industrial stormwater outfalls
- MS4
- Mining outfalls
- Non-contact cooling waters

Potential sources - industrial / commercial -

SIC Code	Code Name Facility
26	Paper and Allied Products
30	Rubber and Misc. Plastics
33	Primary Metal Industries
34	Fabricated Metal Products
37	Transportation Equipment
49	Electrical, Gas and Sanitary Services
1221 & 1222	Bituminous Coal

Source: Belton et al. 2005


When -

- Monitoring
 - Strategy w/n 2 yrs of TMDL
 - VPDES
- How
 - frequent
 - long

Frequency -

- # of samples
 - wet (high)
 - dry (base)
- Type & size
 - Major
 - Minor
 - Industrial stormwater
 - CSO (wet only)


Duration -



Water Quality Standard (WQS) = 1.7 ng/l

Proposed = 0.64 ng/l or 640 pg/l

Duration -



Confirmation + options = pollutant minimization plan (PMP) or storm water pollution prevention plan (SWPPP)



Discussion

Schedule

- Summary
 - Send to TAC
 - Post on web
- Meetings
 - Draft by May 1 & schedule 2nd meeting
 - Final meeting with guidance document July



Guidance Document Outline

TMDL Monitoring and/or Data Collection and Analysis to Characterize Point Source Loadings of Low Level PCBs

- Background
- Objective
- Procedure
 - Facilities
 - Method
 - Frequency and Duration
 - Analytical Requirements
- Laboratories

